

## IoT-Line Precision balance KERN 572



### Technical data

- Large backlit LCD display, digit height 21 mm
- Dimensions weighing surface, stainless steel
  - A  $\varnothing$  106 mm
  - B  $\varnothing$  150 mm
  - C WxD 160x200 mm, see larger picture
- Overall dimensions (without draught shield) WxDxH 180x310x85 mm
- Net weight A, B approx. 2,4 kg
  - C approx. 2,8 kg
- Permissible ambient temperature -10 °C/40 °C

### Accessories

- Protective working cover, scope of delivery: 5 items, KERN 572-A02S05
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01
- External data interface RS-232, interface cable included, KERN YKUP-01
- External data interface USB, interface cable included, KERN YKUP-03
- Extension-Box, KERN YKUP-13
- Loop and hook for underfloor weighing, for models with [d]  $\geq$  0,01 g, KERN 572-A03
- Large glass draught shield with 3 sliding doors for easy access to the items being weighed. Weighing space WxDxH 150x140x130 mm, for models with weighing plate size A, KERN 572-A05


All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications, ideal for the diverse possibilities of Industry 4.0 applications

### Features


- Thanks to the many typical laboratory functions, such as, for example, recipe function, percentage determination, combined with the high level of precision, the KERN 572 is a reliable partner for day-to-day work in the laboratory
- The robust version, typical industrial functions, such as piece-counting, vibrationfree weighing and the large weighing ranges also make these balances ideal for all industrial applications, where a high level of precision is required
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth or Ethernet, for the exchange of data and control commands, without any installation outlay

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers, for details see page 8/9
- Standardised, simplified concept of operation
- Freely programmable weighing unit, e.g. display direct in special units such as length of thread g/m, paper weight g/m<sup>2</sup>, or similar
- The robust aluminium diecast housing maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- Ring-shaped draught shield standard, only for models with weighing plate size A  $\varnothing$  106 mm, weighing space  $\varnothing$ xH 157x43 mm
- Level indicator to level the balance precisely
- Loop for underfloor weighing, standard for models with [d] = 0,001 g
- Protective working cover included with delivery

### STANDARD



### OPTION



### FACTORY



Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Resolution	Weighing plate	Option DAkKS Calibr. Certificate DAkKS KERN
KERN	g	g	g	g	Points		
572-30	240	0,001	0,001	$\pm$ 0,003	240.000	A	963-127
572-31	300	0,001	0,002	$\pm$ 0,005	300.000	A	963-127
572-32	420	0,001	0,002	$\pm$ 0,005	420.000	A	963-127
572-33	1600	0,01	0,01	$\pm$ 0,03	160.000	B	963-127
572-35	2400	0,01	0,01	$\pm$ 0,03	240.000	B	963-127
572-37	3000	0,01	0,02	$\pm$ 0,05	300.000	B	963-127
572-39	4200	0,01	0,02	$\pm$ 0,05	420.000	B	963-127
572-45	12000	0,05	0,05	$\pm$ 0,15	240.000	C	963-128
572-55	20000	0,05	0,1	$\pm$ 0,25	400.000	C	963-128
572-43	10000	0,1	0,1	$\pm$ 0,3	100.000	C	963-128
572-49	16000	0,1	0,1	$\pm$ 0,3	160.000	C	963-128
572-57	24000	0,1	0,1	$\pm$ 0,3	240.000	C	963-128

- 
**Internal adjusting:**  
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)
- 
**Network interface:**  
 For connecting the scale to an Ethernet network
- 
**Suspended weighing:**  
 Load support with hook on the underside of the balance
- 
**Adjusting program CAL:**  
 For quick setting up of the balance's accuracy. External adjusting weight required
- 
**KERN Communication Protocol (KCP):**  
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
- 
**Battery operation:**  
 Ready for battery operation. The battery type is specified for each device
- 
**Easy Touch:**  
 Suitable for the connection, data transmission and control through PC or tablet.
- 
**Rechargeable battery pack:**  
 Rechargeable set
- 
**Memory:**  
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.
- 
**GLP/ISO log:**  
 The balance displays weight, date and time, independent of a printer connection
- 
**Universal plug-in power supply:**  
 with universal input and optional input socket adapters for  
 A) EU, CH, GB  
 B) EU, CH, GB, USA  
 C) EU, CH, GB, USA, AUS
- 
**Alibi memory:**  
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.
- 
**GLP/ISO log:**  
 With weight, date and time. Only with KERN printers.
- 
**Plug-in power supply:**  
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
- 
**KERN Universal Port (KUP):**  
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
- 
**Piece counting:**  
 Reference quantities selectable. Display can be switched from piece to weight
- 
**Integrated power supply unit:**  
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
- 
**Data interface RS-232:**  
 To connect the balance to a printer, PC or network
- 
**Recipe level A:**  
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out
- 
**Weighing principle: Strain gauges**  
 Electrical resistor on an elastic deforming body
- 
**RS-485 data interface:**  
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible
- 
**Recipe level B:**  
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- 
**Weighing principle: Tuning fork**  
 A resonating body is electromagnetically excited, causing it to oscillate
- 
**USB data interface:**  
 To connect the balance to a printer, PC or other peripherals
- 
**Totalising level A:**  
 The weights of similar items can be added together and the total can be printed out
- 
**Weighing principle: Electromagnetic force compensation**  
 Coil inside a permanent magnet. For the most accurate weighings
- 
**Bluetooth\* data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Percentage determination:**  
 Determining the deviation in % from the target value (100 %)
- 
**Weighing principle: Single cell technology:**  
 Advanced version of the force compensation principle with the highest level of precision
- 
**WiFi data interface:**  
 To transfer data from the balance to a printer, PC or other peripherals
- 
**Weighing units:**  
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details
- 
**Verification possible:**  
 The time required for verification is specified in the pictogram
- 
**Control outputs (optocoupler, digital I/O):**  
 To connect relays, signal lamps, valves, etc.
- 
**Weighing with tolerance range:**  
 (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model
- 
**DAkkS calibration possible (DKD):**  
 The time required for DAkkS calibration is shown in days in the pictogram
- 
**Analogue interface:**  
 to connect a suitable peripheral device for analogue processing of the measurements
- 
**Hold function:**  
 (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value
- 
**Factory calibration (ISO):**  
 The time required for Factory calibration is shown in days in the pictogram
- 
**Interface for second balance:**  
 For direct connection of a second balance
- 
**Protection against dust and water splashes IPxx:**  
 The type of protection is shown in the pictogram.
- 
**Package shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram
- 
**Pallet shipment:**  
 The time required for internal shipping preparations is shown in days in the pictogram

\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.