

# SAUTER SW 1000



Professional Class I sound level meter in premium quality



Date of creation: 02.10.2026

| Category                              |                                     |
|---------------------------------------|-------------------------------------|
| Brand                                 | Sauter                              |
| Product category                      | Environment/<br>Occupational safety |
| Product group                         | Sound level meter                   |
| Product family                        | SW                                  |
| Measuring System                      |                                     |
| Frequency range [Max]                 | 20 kHz                              |
| Microphone sensitivity                | 50 mV/Pa                            |
| Frequency range [Min]                 | 10 Hz                               |
| Sound level [Min] (dB)                | 20 dB                               |
| Sound level [Max] (dB)                | 134 dB                              |
| Sound level measuring modes           | Lp                                  |
|                                       | Leq                                 |
|                                       | Ln                                  |
|                                       | Lcpeak                              |
| Sound level methods of evaluation     | A                                   |
|                                       | C                                   |
|                                       | Z                                   |
|                                       | B                                   |
| Units                                 | dB                                  |
| Sound level meter class               | Class 1                             |
| Readability sound [d] (dB)            | 0,1 dB                              |
| Construction                          |                                     |
| Dimension housing (W×D×H)             | 210×80×40 mm                        |
| Dimensions device (W×D×H)             | 300×80×36 mm                        |
| Dimensions completely mounted (W×D×H) | 340×80×40 mm                        |

|                          |         |
|--------------------------|---------|
| Material housing         | plastic |
| Material display housing | plastic |

| Functions              |   |
|------------------------|---|
| Hold function          | ✓ |
| Peak function          | ✓ |
| Analogue signal        | ✓ |
| Memory function        | ✓ |
| Limit-setting function | ✓ |

| Power Supply                                                              |                                                                          |
|---------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Supplied power supply                                                     | Power supply & battery function (battery not included)                   |
| Power supply type                                                         | Power adapter                                                            |
| Plug-in power supply / adapter for countries - included with the delivery | EURO                                                                     |
| Plug-in power supply / adapter for countries - optional                   | EURO                                                                     |
|                                                                           | AUS                                                                      |
|                                                                           | UK                                                                       |
|                                                                           | US                                                                       |
| Input voltage power supply / power [Max]                                  | CH                                                                       |
|                                                                           | 100 V - 240 V, 50 / 60 Hz                                                |
| Power supply cable removable                                              | removable                                                                |
| Input voltage device / power [Max]                                        | 12 V, 1 A                                                                |
| Power socket for mains adapter                                            | Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,5 mm |
|                                                                           |                                                                          |
| Battery / accumulator type                                                | Alkali(-Manganese)                                                       |
| Battery                                                                   | 4×1.5 V AA                                                               |
| Battery connection                                                        | Pad + Spring                                                             |
| Battery operating time                                                    | 10 h                                                                     |
| Battery capacity                                                          | 38 mAh                                                                   |
| Battery voltage                                                           | 3 V                                                                      |
| Battery - Number of cells                                                 | 1                                                                        |
| Battery - Individual weight                                               | 0,8 g                                                                    |
| Battery - Lithium content                                                 | 12 mg                                                                    |

| Environmental conditions  |        |
|---------------------------|--------|
| Use temperature [Min]     | -10 °C |
| Use temperature [Max]     | 50 °C  |
| Storage temperature [Min] | -10 °C |
| Storage temperature [Max] | 60 °C  |

# SAUTER SW 1000



Professional Class I sound level meter in premium quality

## Services (optional)

|                                        |         |
|----------------------------------------|---------|
| Article number for DAkkS calibration   | 963-281 |
| Article number for factory calibration | 961-281 |

## Packing & Shipping

|                              |                |
|------------------------------|----------------|
| Delivery time                | 1 d            |
| Dimensions packaging (W×D×H) | 405×305×100 mm |
| Shipping method              | Parcel service |
| Net weight approx.           | 0,40 kg        |
| Gross weight approx.         | 1,4 kg         |
| Shipping weight              | 2,5 kg         |
| Shipping volume weight       | 2,5 kg         |

## Product information

|                      |                          |
|----------------------|--------------------------|
| GTIN/EAN number      | 4045761200845            |
| Trade number         | 90278990                 |
| Warranty Time        | 36 mon                   |
| REACH classification | no prohibited substances |

## Pictograms

### STANDARD



### OPTION

