

SAUTER BSWA-01



Adjustment device for regular adjustment of the sound level meter



Date of creation: 03.10.2026

Category

Brand	Sauter
Product category	Measurementstechnology
Product group	Accessories for sound level measurement

Measuring System

Frequency range [Max]	1010 Hz
Frequency range [Min]	990 Hz
Sound level [Min] (db)	94 dB
Sound level [Max] (db)	114 dB
Units	dB
Tolerance (% of [Max])	0,2%
Sound level meter class	Class 1 Class 2

Construction

Dimension housing (W×D×H)	70×70×50 mm
Dimensions completely mounted (W×D×H)	70×70×50 mm
Material housing	plastic

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery capacity	2.900 mAh
Battery voltage	3 V
Battery - Number of cells	2
Battery - Individual weight	23 g
Battery - Total weight	46 g

Battery - Construction	Individual cells
Battery capacity (Wh)	4,35 Wh
Battery - Lithium content	0 g

Environmental conditions

Use temperature [Min]	-10 °C
Use temperature [Max]	50 °C
Storage temperature [Min]	-10 °C
Storage temperature [Max]	60 °C

Services (optional)

Article number for DAkkS calibration	963-291
Article number for factory calibration	961-291

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	145×105×70 mm
Shipping method	Parcel service
Net weight approx.	0,10 kg
Gross weight approx.	0,25 kg
Shipping weight	0,245 kg
Shipping volume weight	0,2 kg

Product information

GTIN/EAN number	4045761220201
Trade number	90278990
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD

